

## WHAT IS CLAIMED IS

1. An electromagnetic connector for high voltages  
5 and large currents, comprising a primary winding (12)  
connected to a high-voltage, large-current power supply (1),  
a secondary winding (14) connected to an electromagnetic  
forming coil (2), and a magnetic core (16) for guiding the  
magnetic flux produced by the primary winding, into the  
10 secondary winding, wherein

the magnetic core (16) comprises a primary core (16a)  
with a primary winding and a secondary core (16b) with a  
secondary winding,

the primary core and the secondary core are  
15 magnetically connected together by putting them in contact  
or in close proximity, and separated each other when the  
connector is disconnected.

2. The electromagnetic connector for high voltages  
and large currents, specified in Claim 1, wherein the  
20 magnetic core (16) is a closed rectangle in shape, and the  
primary core (16a) and the secondary core (16b) comprise U-  
shaped structures produced from the rectangle by cutting  
the rectangle into two parts.

3. The electromagnetic connector for high voltages  
25 and large currents specified in Claim 2, wherein the cut  
surfaces of both the U-shaped structures are in close  
contact with each other or located close to each other when  
connected, and can be configured to keep a space between

100764330-00140002

them when they are disconnected.

the two parts cut as above can be in close contact with each other or located close to each other when connected, and can be configured to keep a space between  
5 them when they are disconnected.

4. The electromagnetic connector for high voltages and large currents, specified in Claim 1, wherein the primary winding (12) and the secondary winding (14) are wound on each core (16a or 16b) in such a manner that both  
10 windings (12, 14) overlap each other concentrically, when the connector is connected.

5. The electromagnetic connector for high voltages and large currents, specified in Claim 1, wherein the magnetic core comprises silicon steel sheets, a ferrite  
15 material or an amorphous material.

6. The electromagnetic connector for high voltages and large currents, specified in Claim 1, wherein the primary winding (12) and the secondary winding (14) are molded separately in a plastic resin.